

LUX M10



KUBOTA Z482, 2 CYL. ENGINE
1500 RPM LIQUID COOLED



VERTICAL TELESCOPIC MAST
8.5 m MAX HEIGHT
LIFETIME WARRANTY



RATED OUTPUT: 3.5kVA - 230V
OUTLET SOCKET: 1.3kVA - 230V



FUEL CONSUMPTION 0.55 l/h
145 hs. RUNNING TIME



4x150 W LED LAMPS
3000 m² ILLUMINATED AREA
GUARANTEED 50.000 hrs



350° MAST ROTATION
ADJUSTABLE FLOODLIGHT



GALVANIZED METAL BODY
80 µm POWDER COATING



SERIES



MADE IN
ITALY



LUXTOWER 
lighting towers

ROUGH DIMENSIONS & WEIGHT

Dimensions min.	mm	2390 X 1380 X 2580
Dimensions max.	mm	2390 X 2370 X 8500
Total weight without fuel	Kg	690

FEATURES


Rotation		350°
Floodlight	W	4 X 150
Lamps		LED
Wind stability	Km/h	110
Options		Light sensor Main/generator switch Bunder tank

ALTERNATOR

Model		Linz Alumen SP-E1C
Frequency	Hz	50 - 60
Degree of protection		IP23
Rated output	kVA/V	3.5 - 230
Auxiliary outlets	kVA	1.3

ENGINE

Model		Kubota Z482 - 2 cyl - liquid cooled
Fuel		Diesel
r.p.m.		1500
Noise Level	db at 7 meters	65
Tank capacity	l	80
Running time	h	145
Fuel consumption	l/h	0.55

 **5 LUX MIN.**


ILLUMINATED AREA

3000 m²

- 5 m range
- 10 m range
- 20 m range
- 30 m range



40'' HC container



11 units per truck

