

# Technical Data

GML800+ M-Series	GML800+/10/M	GML800+/15/M	GML800+/20/M	GML800+/25/M
Working height - Standard Fork up:	3,30 m	4,70 m	6,10 m	7,50 m
Transport position - Height/Length/Width:	1,98/1,10/0,81 m	1,98/1,10/0,81 m	1,98/1,10/0,81m	1,98/1,10/0,81m
Working position - Height/Length/Width	1,98/1,94 /0,81 m*	1,98/1,94/0,81m*	1,98/1,94/0,81 m*	1,98/1,99/0,81 m*
Safe working load (load center: 28 cm):**	900 kg	850 kg	800 kg	800 kg
Weight Chassis + outrigger:	308 kg	344 kg	382 kg	444 kg
K-Models additional:	6,8 kg	6,8 kg	6,8 kg	6,8 kg
Counterweights with Box:	212 kg	212 kg	212 kg	212 kg

\*Outrigger backwards. Outrigger forwards = 2,80 m. \*\* Without Loading device.

GML800+ AC-Series	GML800+/10/AC	GML800+/15/AC	GML800+/20/AC	GML800+/25/AC
Working height - Standard Fork up:	3,30 m	4,70 m	6,10 m	7,50 m
Transport position - Height/Length/Width:	1,98/1,10/0,81 m	1,98/1,10/0,81 m	1,98/1,10/0,81 m	1,98/1,10/0,81 m
Working position - Height/Length/Width	1,98/1,94 /0,81 m*	1,98/1,94/0,81 m*	1,98/1,94/0,81 m*	1,98/1,94/0,81 m*
Safe working load (load center: 28 cm):**	900 kg	850 kg	800 kg	800 kg
Weight Chassis + outrigger:	326 kg	362 kg	427 kg	462 kg
AC-Drive:	230/110V	230/110V	230/110V	230/110V
K-Models additional:				
Counterweights with Box:	212 kg	212 kg	212 kg	212 kg

\*Outrigger backwards. Outrigger forwards = 2,80 m. \*\* Without Loading device.

GML800+ DC-Series	GML800+/10/DC	GML800+/15/DC	GML800+/20/DC	GML800+/25/DC
Working height - Standard Fork up:	3,30 m	4,70 m	6,10 m	7,50 m
Transport position - Height/Length/Width:	1,98/1,10/0,81 m	1,98/1,10/0,81 m	1,98/1,10/0,81 m	1,98/1,10/0,81 m
Working position - Height/Length/Width	1,98/1,94/0,81 m*	1,98/1,94/0,81 m*	1,98/1,94/0,81 m*	1,98/1,94/0,81 m*
Safe working load (load center: 28 cm):**	900 kg	850 kg	800 kg	800 kg
Weight Chassis + outrigger:	309 kg	345 kg	409 kg	445 kg
AC-Drive:	2x 12V/105Ah	2x 12V/105Ah	2x 12V/105Ah	2x 12V/105Ah
K-Models additional:				
Counterweights, Box, Battery Carrier	221 kg	221 kg	221 kg	221 kg

\*Outrigger backwards. Outrigger forwards = 2,80 m. \*\* Without Loading device.

GML800+ Wheel load	GML800+ /Std	GML800+ /K
Safe working load up to 400 kg	200 kg/caster	500 kg/at the front
Safe working load up to 600 kg	250 kg/caster	750 kg/at the front
Safe working load up to 900 kg	300 kg/caster	1,000 kg/at the front